

---

## ARENAS EGYPCIAS. Decorative coating.



---

### Technical Specification

---

#### DESCRIPTION

Vinyl decorative painting that by adding our dyes (TINTURAS JAFEP) it produces sandy effect finishes, friction resistant and good washability and resistance to light and to harsh weather depending on the pigmentation.

#### TECHNICAL CHARACTERISTICS

Appearance: Sandy  
Density: 1.5 gr./cm<sup>3</sup>  
Drying: 2-3 hours approximately  
Thinning: Water  
Coverage: 5 m<sup>2</sup>/ kg.  
Tinting: Tinturas Jafep (dyes)  
Application temperature higher than 8 °C.

#### APPLICATION

Painting and decoration of new or old plaster, gypsum, etc brickwork supports that are clean and smooth and previously painted with Fondo Satinado (Satin Undercoat).

#### INSTRUCTION FOR USE

- In every case, prime with FONDO (undercoat). Apply one or two coats depending on the requirements.
- Colour Arenas using the desired shade of Tinturas (dyes).
- Using a short-hair glove, spread the product using long straight or circular strokes to get different finishes.

In general, we recommend:

- Do not apply at temperatures below 8 °C.
- Do not expose the packaging to extreme temperatures.

#### SUBMITTALS

Plastic packaging of 5 Kg.

- Tinturas (dyes) : plastic packaging of 25 mL.

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.