

## Technical Data Sheet

### ColorFill Solvent

#### Product Description

ColorFill Solvent is an acetone based solvent used to clean excess dried ColorFill from around a joint.

#### Benefits

- Effective solvent for ColorFill
- Fast evaporating
- Leaves no residue

#### Applications

Cleaning of excess ColorFill from around a joint.

#### Directions of Use

Apply ColorFill Solvent to a clean, lint free cloth and rub excess ColorFill until dissolved and removed, taking care not to remove any ColorFill from the joint.

Take care to avoid unintended contact with surrounding materials, as ColorFill Solvent will attack some plastics and painted surfaces.

#### Surface Preparations and Finishing

- Application temperature +5°C to +30°C (environment and substrate).

#### Additional information

Volatiles	100%
Flash Point	-17°C
Shelf Life	2 years @ 20°C
Specific Gravity	0.97

#### Appearance

- Clear, colourless, low viscosity liquid

#### Packaging

- 20ml, 150ml bottle

#### Shelf Life

In unopened original packaging between +5°C and +25°C, shelf-life till 24 months after production date, stored in a dry place.

#### Health & Safety

Keep in a cool well-ventilated area away from sources of ignition.

Keep away from children at all times.

Keep containers sealed.

Use in a well-ventilated area.

Avoid contact with skin and eyes

For further information, please read the product SDS.

Note: The data, information and values contained in this Technical Data Sheet have been obtained by conducting various tests in a controlled laboratory environment, and should be used for guidance purposes only. Although we believe them to be reliable and accurate, users should always conduct their own tests in their specific working conditions to ensure that the product is suitable and effective for use. It is the user's sole responsibility to determine the suitability of the product for the application. Unika Color Products Ltd. Cannot be held responsible for the results of procedures undertaken elsewhere, nor for the safeguarding of personnel or property, all of which is the duty of the user. Suitability of products or methods is discretionary. Therefore, warranties or implied usage obligations should not be attributed to and are not the responsibility of Unika Color Products Ltd. Unika Color Products Ltd. are not liable for any financial loss or other damages incurred by the user as a result of the use of this product.