



## Dulisol Hydro

One component water based acrylic floor coating



**Covering Power:** 12-14 m<sup>2</sup>/lt



**Drying:** ½ - 1 hour



**Dilution:** 8-10% on volume with water using brush/roller, or up to 15% when using spraygun



**Recoatability:** 5-6 hours



**Packing:** 750ml, 2,5lt

**Application:** Brush, Roller, Airless Gun

### GENERAL CHARACTERISTICS

One component water-based paint for paved, concrete floors and alkaline surfaces. Due to its special composition, it is suitable for indoor and outdoor floors with light traffic. It offers great coverage, smooth application, very good adhesion and high weather resistance.

### TECHNICAL CHARACTERISTICS

<b>Texture</b>	Satin
<b>Specific weight</b>	1,23 ± 0,02 kg/lt
<b>Covering power</b>	12 -14 m <sup>2</sup> /lt per coat, depending on floor type
<b>Dilution</b>	8 - 10 % on volume with water for application by brush or roller and 15% on volume for spray application.
<b>Drying</b>	½-1 hours touch free.
<b>Recoatability</b>	Recoatable in 5-6 hours after application. These times prolong under cold and wet weather conditions.
<b>Walkability</b>	4-8 hours after application depending on weather conditions.
<b>VOC class</b>	“One pack reactive performance coating. Floor coatings”. Type WB. VOC limit =140 gr/lt. Max VOC of product ready for use= 60 gr/lt. VOC: organic volatile compounds with boiling point < 250° C
<b>Wash ability</b>	At least 3-4 weeks after application with gentle cleansers. It is recommended not to use water under pressure.
<b>Shades</b>	Available at thousands color shades via VECHRO's tinting system



## SURFACE PREPARATION

To make sure of a successful paint adhesion, the surface to be painted has to be cleaned of dust, oil, cropped paints, rust and dampness. Sandpaper well.

## APPLICATION

Stir well before use. On a properly prepared dry surface apply one coat Dulisol Hydro in the appropriate dilution. When it dries apply, if necessary, a second coat.

## CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with water and soap. Avoid washing materials entering into water-courses.

## APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

## STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

## LABELLING

More information in Safety Data Sheets (MSDS).

## SAFETY

Read the tag on the back side of the product. Keep out of the reach of children.

The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.

