# PETREX 5 PLAIN COATING Technical information



#### **DESCRIPTION**

Exterior coating. Water-proof and washable. High level of resistance to weather, saltpetre and abrasion. It has I.N.C.E. certification

### **TECHNICAL CHARACTERISTICS**

Nature: Acrylic copolymers

Colour: White and all the colours from the sample colour chart

Appearance: Matt

Specific weight: 1.35 +- 0.3 gr./ cm Drying: 30 minutes approximately.

Diluent: Water

Application: Brush, roller, spray gun or airless gun (adjusting density) Performance: Between 5 and 8 m²/kg. (depending on the surface)

Tinting: JAFEP Dyestuffs Second coat: After 5 hours

## **APPLICATION**

For decorating and protecting exteriors: façades, yards, exterior walls, etc.; but also, due to its extraordinary smoothness, it can be used to decorate interiors, particularly in pastel shades, with a magnificent quality washable finish and unbeatable performance.

## **INSTRUCTIONS FOR USE**

On clean new surfaces that are dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, diluting by up to 20% for the first coat.
- Plaster, gypsums or wood: Sealing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.
- Powdery surfaces, first apply a base coat using fixative.

#### On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

# In general, we recommend:

- Do not apply at temperatures below 5° C.
- Do not expose the containers to extreme temperatures.

Tel.: 967 44 05 96 – 967 44 00 36 – 967 44 06 45 Fax: 967 44 26 12 E-mail: dpto\_tecnico@jafep.com

## **PRESENTATION**

Metal containers of: 3.5 Litres 15 Litres

## **ENVIRONMENT FRIENDLY**

# **Kyoto 2012**

This product fulfills the restrictions on signed emissions to the atmosphere in the protocol of Kyoto

## EU COV's

VOC highest level EU for this product (Cat A/c): 75 g/l (2007) / 40 g/l (2010). It contains 40 g/l VOC at maximum.

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.

Tel.: 967 44 05 96 – 967 44 00 36 – 967 44 06 45 Fax: 967 44 26 12 E-mail: dpto\_tecnico@jafep.com