



ROAD MARKING PAINT

Technical information

DESCRIPTION

Solvent based matt acrylic paint especially developed for painting road markings. High resistance to wear, quick drying and is driveable after several hours.

TECHNICAL CHARACTERISTICS

Nature: Acrylic
Colour: White, red and yellow
Appearance: Matt
Density: $1.60 \pm 0.05 \text{ gr./cm}^3$
Viscosity: Thixotropic
Drying: 20 - 30 minutes
Second coat: 2-3 hours
Diluent: JAFEP Chlorinated Rubber Solvent
Application: Brush, roller or spray
Performance: 5 - 6 m²/Kg./coat

APPLICATION

For painting horizontal lines such as zebra crossings, entrances, lanes, etc.
On concrete, asphalt, cement and stone surfaces.

INSTRUCTIONS FOR USE

Remove the content of the container properly, diluting it by between 5% and 20% according to the method of application. Apply one or several coats of paint liberally in order to achieve sufficient thickness.

In general, surfaces should be free from dust, grease, wax and be totally dry. Concrete and cement should be completely set.

On previous coats of paint in good condition: wash, sand and paint.

If the paint is in poor condition: completely remove and proceed as per new surfaces.

It is important not to paint in high temperatures or if the surface is very hot as the rapid evaporation of the solvent may result in blistering and poor paint adhesion.

SUBMITTALS

Metal containers of: 4 Litres; 18 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.