
METALLIC PAINT

Technical Data Sheet



DESCRIPTION

Water-based metallic paint for interior and exterior use, with easy application. It is washable and it produces a smooth metal effect or with back lights.

TECHNICAL CHARACTERISTICS

Touch dry: 40 minutes.

Total 2 – 3 days.

Diluent: Water

Coverage: From 10 to 12 m²/ L (depending on surfaces and application way)

Colours ready for use

Application temperature higher than 8°C.

APPLICATION

It is applied on all kind of surfaces that are clean, dry and free from dust and grease.

It can be also used like dyestuffs for high decoration products (Tierras Rodantinas, Cera Muralia, Arenas Egypcias, etc.)

INSTRUCTION FOR USE

Plaster: Dilute the first coat at 20%. Second coat, ready for use.

Wood: Sealer with the suitable product (Multiusos al agua Jafep (Water-based multipurpose Jafep))

Iron: Prime with the suitable product (Multiusos al agua Jafep (Water-based multipurpose Jafep))

Smooth effect: Apply using a brush or a short-haired or a 0 pore foam roller.

If we want to apply using a spray or airless, adjust viscosity.

Textured effect: Using a brush, apply with alternative strokes depending on the draw we want to do.

In general, we recommend:

- Do not apply at temperatures below 8 °C.
- Do not expose the packaging to extreme temperatures.

SUBMITTALS

Metallic paint: plastic packaging 1L.

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.