

Ficha Técnica

Matt Emulsion Paint Exterior/Interior 900 Multicolor Base for Tinting Systems



Acrylic paint

Versión: 30/10/2023



Descripción

Excellent quality acrylic emulsion paint, specially designed in three bases: P, D, TR to obtain finishes in different color tones for all types of decoration, restoration and maintenance work.

Propiedades

- Suitable for exteriors/interiors
- Quick dry
- Excellent washability

Certificados de empresa





Datos técnicos

Datos de identificación del producto

Color	Color charts NCS, RAL, ASF, etc.
Aspecto	Matt
Naturaleza	Acrylic copolymers
Peso específico	1,45-1,60 gr/cm ³

Datos de aplicación del producto

Herramienta	Brush, roller, spray gun or airless
Rendimiento	12-14 m ² /L/Coat
Diluyente	Water
Limpieza	Water
Repintado	6-8 hours
Secado	30 minutes (Touch)

Prestaciones finales

Resistencia al frote en húmedo	Class 1 (according to UNE-EN 13300 Standard); >10,000 cycles UNE 48243
--------------------------------	--

Dónde aplicarlo

On exterior surfaces with cement supports, fiber cement concrete, etc. And interiors of plaster, prefabricated, wood and suitably treated metals.

Precauciones



- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or under direct sunlight.
- Avoid using different batches in the same work or mix the current pot with the next 50% to reduce the normal differences between batches.

Modo de empleo

It can be applied with a brush, roller or spray gun.

All supports will be clean, dry, free of grease and saltpeter.

If the surface is new, it will be applied directly, but diluting the first coat with 10-15%.

If it is very absorbent, it will be fixed previously.

If the surface is already painted and in good condition, it will also be applied directly, but if not, the paint must be removed to proceed as a new surface.

Due to the matt finish, a tinting chart with the same or similar finish to the product to be tinted must be used to avoid differences in the results caused by differences in gloss (RAL for Glossy, Jafep Standard or NCS for Matte finishes, etc.)

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacture: 2 years.

Formatos

Containers: 750 ml, 4 & 15 L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com