

## TECHNICAL DATA SHEET

# PLAC-PLAY 504

Rev.1 Pag1/1



**AC Valquimia, S.L.U.**  
**info@valquimia.com**  
AC Valquimia, S.L.U.  
T.fijo: 865 77 86 86  
P.I. El Pastoret, C/ Galicia 11A  
03640 Monóvar (Alicante-Spain)

### DESCRIPTION:

PLAC-PLAY 504 is a rubbercrumb tile specially apt for outdoor children playgrounds.

### APLICACIÓN:

- 1) Use our polyurethane adhesive ENETAK 652. Tile and substrate should not be wet (humidity lower than 5%) in the moment of adhesion.
- 2) Pavement substrate must be firm, clean (free of dust and oil) and dry. Leveled within an error margin of 4%
- 3) Restate previously the tiles, before applying adhesive

### ESPECIFICACIONES:

- 1) Ideal in playgrounds thanks to impact absorption, nonskid, atoxic qualities.
- 2) Dimensions: 500x500x40 mm. Colours available: red, green, grey, black.
- 3) Hardness 49-59 IRHD
- 4) Density 1.01-1.07 g/cm<sup>3</sup>
- 5) Abrasion resistance :  
339 mm<sup>3</sup> ± 10% (without ageing)  
271 mm<sup>3</sup> ± 10% (with ageing: 7 days at 70°C y 100% humidity)
- 6) Outdoor resistance (rain, UV,...) It will decompose with vegetal oils.
- 7) Other applications: walks, gymnasiums, insonorization, wall protection in garages, vibration isolation, ...

This information corresponds to our current state of knowledge and serves as guidance on our products and their possible applications. With this and other technical, we are just trying to inform and advise but without assuming commitment on our own. It is always advisable to test the application.

