



Powerful Cleaner to Remove Oxidation Staining from Surfaces

PRODUCT DESCRIPTION

PureKleen-RR is a powerful acid treatment designed to remove any surface oxidation

PureKleen-RR: is for use on

Tile, porcelain, natural stone, granite worktop and marble (not polished) surfaces

APPLICATION

- ⇒ Test first on the surface is essential to establish the correct dwell time. This will ensure the underlying substrate is not affected.
- ⇒ Brush or roller and then leave it to soak, allowing 5-15 minutes to act.
- ⇒ Be careful to mask off and protect surfaces that are not intended to be treated.
- ⇒ Thoroughly wash the treated surface surface with water and clean off any remaining residues
- ⇒ Once cleaned it is recommended that surfaces are quickly protected with PureScape as soon as the surface is visibly dry.

PACKAGING

1L and 5L containers

TECHNICAL DATA

- Physical State at 20 °C : Liquid
- Appearance : Colourless
- pH : 1
- Boiling point [°C] : 100 °C
- Density : 1.00
- Solubility in water [vol/vol] : Fully soluble
- Flash Point [°C] : Not applicable
- VOC : 10 g/l
- Odour : Mild characteristic odour



Dark: Untreated.

Pale: Treated

Limestones



Left: Untreated

Right: Treated

COVERAGE RATE

The figures below are approximate and should be used only as a general guideline: 4-8 m² / litre

EQUIPMENT CLEANING

Immediately after you have finished clean all tools and equipment with water.

STORAGE & SHELF LIFE

Keep in a dry place (between 5°C and 30°C).

Storage: 24 months following the production date when kept in the original unopened container.

RECOMMENDATIONS

- Wear protective gloves and glasses, and appropriate clothing whilst using the product.
- Do not dilute or mix with another product .
- Do not allow the applied product to dry.
- Do not apply during rain or frost and when surface and air temperature is < 5°C and > 30°C.

HEALTH & SAFETY

See Material Safety Data Sheet before use.

Important: The content of this documentation is based on our experience of the product. Rocan Products Ltd guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with Rocan's products or bad weather conditions. For further information, refer to the safety data sheet.

ROCAN PRODUCT CODE: R-0013

Date of last update: 09.06.15



www.rocan.co.uk — Tel: 01256-211278—sales@rocan.co.uk
Rocan Products Ltd, Grove House, Lutyens Close, Basingstoke, Hants RG24 8AG
Company No 8933542 Registered in England & Wales

