

PTFE TAPE

12 m x 12 mm x 0.075 mm

DESCRIPTION

Polymerized laminated Tetrafluoroethylene (PTFE)

PROPERTIES

- Compatible with all usual pipe materials, chemicals, acids, alkalis, solvents and gases.
- Certified by WRAS (UK) for drinking water.

APPLICATIONS

- Sealing of plastic or metallic threaded accessories in piping systems for fluids.
 - Sealing of deposits and lines of fuel, air conditioning units, radiators, discharge lines and with cooling fluids, hydraulic and braking systems.
 - Temperature range: from $-20\text{ }^{\circ}\text{C}$ to $125\text{ }^{\circ}\text{C}$.
-

TECHNICAL CHARACTERISTICS

Density	Approx. 0.35 g/mL
Thickness	0.075 mm
Length	12 m
Width	12 mm

INSTRUCTIONS FOR USE

We recommend rolling the PTFE tape clockwise around the male thread – turns are indicated below:

Number of turns depending on the thread
1 turn minimum at thread $\frac{1}{4}$ "
2 turns minimum from $\frac{1}{4}$ " to $\frac{1}{2}$ "
3 turns minimum from $\frac{1}{2}$ " to 1"

This procedure must be undertaken with a minimum tension, so the tape adopts the shape of the thread, pulling the tape to cut it once the application is finished.

STORAGE

Keep inside the original container in a cool, dry place, avoiding direct exposure to sunlight.

PRESENTATION Visit www.unecol.com

The above mentioned data are based on our better experience and knowledge, but should be understood as specifications. The end user is responsible for verifying the suitability of the information provided, according to the specific use of the product

Approval Number: 1609550
Test Report: M106192



12th February 2018

Unecol Adhesive Ideas, S.L.
Avda. de la Foia, 44,
46440 Almussafes,
Spain

Water Regulations Advisory Scheme Ltd.
Unit 13,
Willow Road,
Pen y Fan Industrial Estate,
Crumlin,
Gwent,
NP11 4EG

WATER REGULATIONS ADVISORY SCHEME LTD. (WRAS)
MATERIAL APPROVAL

The material referred to in this letter is suitable for contact with wholesome water for domestic purposes having met the requirements of BS6920-1:2000 and/or 2014 'Suitability of non-metallic products for use in contact with water intended for human consumption with regard to their effect on the quality of the water'.

The reference relates solely to its effect on the quality of the water with which it may come into contact and does not signify the approval of its mechanical or physical properties for any use.

POLYTETRAFLUOROETHYLENE (PTFE) - COMPONENTS.

5294

'CINTAS PTFE'. White coloured PTFE tape manufactured by press strip roller. For use with water up to 60°C.

APPROVAL NUMBER: 1609550

APPROVAL HOLDER: UNECOL ADHESIVE IDEAS, S.L.

The Scheme reserves the right to review approval.

Approval 1609550 is valid between September 2016 and September 2021

An entry, as above, will accordingly be included in the Water Fittings Directory on-line under the section headed, "Materials which have passed full tests of effect on water quality".

The Directory may be found at: www.wras.co.uk/directory

Yours faithfully

A handwritten signature in black ink, appearing to read 'Jason Furnival', written in a cursive style.

Jason Furnival
Approvals & Enquiries Manager
Water Regulations Advisory Scheme

WRAS MATERIAL APPROVAL - MATERIALS WHICH HAVE PASSED FULL TESTS OF EFFECT ON WATER QUALITY

The material referred to in this letter is suitable for contact with water for domestic purposes. **Approval of this material does not signify the approval of its mechanical or physical properties for any use.**

Manufacturers or applicants may only quote in their sales literature terms which are used in this letter, namely that; 'the material as listed, having passed the tests of effect on water quality, is suitable for use in contact with wholesome water'

This may be abbreviated to 'Water Regulations Advisory Scheme - Approved Material' or 'WRAS Approved Material'.

The scope of an Approval does not extend to rebranded materials unless otherwise agreed by the Scheme.

Use of the WRAS Approved Material Logo

Approval holders may use the WRAS Approved Material logo and make reference to any approval issued by WRAS Ltd. in respect of a particular material or range of materials provided the approval is, and remains valid.

Approval holders are entitled to use the logo on the packing, promotional literature and point of sale advertising Approved Materials.

Modifications to existing Approvals

It is a condition of WRAS Material Approval that NO changes or modifications to the Approved Material, be made without the Approval Holder first notifying WRAS Ltd. Full details of the proposed changes must be provided to the Scheme. Failure to comply with this condition will immediately invalidate a previously granted Approval.

Re-Approval

WRAS will write to you 1 year before the approval expires asking whether you would like to renew it. Please complete the relevant section of the MA3 application form which will be included with the letter and return to WRAS (via e-mail or post).

Please note it is the responsibility of the Approval Holder to ensure the Approval remains valid. WRAS Ltd. accepts no liability for the delay in granting approval where this is caused by circumstances outside of the Scheme's control.