

Ficha Técnica

Jafep Anti-Woodworm

Jafep Anti-Woodworm

Versión: 21/09/2023



Ventajas

- Helps preserve wood
- Nourishes the wood
- Not drying
- High resistance to the elements
- Long duration
- Does not leave film

Descripción

Colorless water-based preparation for use with solvent-based or water-based painting systems, which acts in depth preventing the appearance of woodworm. It does not dry out the wood or leave a film.

Propiedades

Jafep Anti-Woodworms is a water-based product that is ready to use and easy to apply. Protects wood against wood-destroying fungi and blue-blue fungi, against insects and parasites and preventing the appearance of woodworm.

Efficacy tests have been carried out in accordance with European Regulations:

- EN 152. Wood protectors. Determination of the preventive effectiveness of a protective treatment against wood bluing fungi.
- EN 46. Determination of effectiveness against insects, together with accelerated aging tests: EN 73. Evaporation aging test and EN 84. Washing test.
- EN 118. Wood protectors. Determination of preventive efficacy against reticulitermes species (European termites), together with accelerated aging tests: EN 73. Evaporation aging test and EN 84. Washing test.

Certificados de empresa





Datos técnicos

Datos de identificación del producto

Color	Colorless
Aspecto	Liquid
Naturaleza	Biocide
Peso específico	0,95-1,05 g/cm ³

Datos de aplicación del producto

Herramienta	Brush, Roller
Repintado	24 hours
Secado	Dust drying: 1-2 hours, total drying: 24 hours

Prestaciones finales

Aspecto Aplicado	Does not leave film
------------------	---------------------

Dónde aplicarlo

Jafep Anti-Woodworm is intended for the treatment of exterior wood such as windows, exterior doors, siding, fences, etc. Direct contact with the soil and aquatic environment should be avoided.

Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply if the relative humidity is greater than 80%.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Use only in doses of 200 ml/m² with application by brush and/or roller.
- Do not use on wooden pieces in direct contact with food or feed.



- Do not use indoors, treated wood should only be used indoors for exterior window and door frames.
- Do not use near aquatic environments such as streams, lakes, etc.

Modo de empleo

The application must always be on exteriors, both of Jafep Anti-Woodworm and its subsequent finishing layer (Only for Class 2 and 3 uses according to DS/EN335:2013).

Clean, sand and remove dust. In the case of painted wood, strip it completely. Apply with a brush or roller. Apply without diluting and after 24 hours of application, always finish with a finishing product (varnish, lasur, etc.).

A dosage of 200 ml product/m² is recommended, without exceeding it.

To clean the tools, use mild soap and water.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers: 750 ml & 2,5 L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA

DUBAI

ESPAÑA

MARRUECOS

POLONIA

UCRANIA



www.jafep.com
jafep@jafep.com