

Ficha Técnica

Aqua Acrylic Varnish

Water-based acrylic varnish

Versión: 22/08/2023



Descripción

Water-based varnish for use mainly on wood outdoors, although it can also be applied indoors. Protects and decorates in extreme conditions and environments. Contains filter additives that protect from UV rays.

Propiedades

- Good adhesion
- Good brushability
- Good penetration
- High resistance to abrasion, blows and friction
- Great durability
- Protection in extreme environments with sunscreen
- Fire resistance test: B-s1, d0

Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	Colorless, Oak, Mahogany, Pine, Teak and Walnut. And in the multicolor system all Coltec-Wood colors
Aspecto	Gloss (colors and colorless) and Satin (colorless)
Naturaleza	Acrylic Dispersion

Datos de aplicación del producto

Herramienta	Brush, Spray or Airless
Rendimiento	For Gloss: 12-14 m ² /L/Coat; For Satin: 8 - 12 m ² /L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	3 hours
Secado	30 - 45 minutes (aprox.)

Dónde aplicarlo

Varnishing of doors, windows and in general, any type of exterior woods

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current bottle with the next one at 50% to reduce the normal differences between batches.

Modo de empleo

- NEW WOOD:

Clean, sand thoroughly and remove dust. It is advisable to apply a first coat of Water-Based Penetrating Primer for Wood. Apply one or more unthinned coats as a finish, sanding between coats. Important: In tropical woods such as chestnut, oak, etc. which are rich in tannins, it is advisable to clean them beforehand with a cloth soaked in non-greasy solvents such as acetone; on the other hand, resinous woods such as pine must be cleaned with greasy solvents such as white spirit.



- VARNISHED WOOD:

Sand gently and clean. Apply one or two coats undiluted. If it is in very bad condition, the existing varnish will be removed and proceed as new wood.

Almacenamiento

- In its original closed container, at non-extreme temperatures and humidity.
- Keep away from direct sunlight.
- Recommended maximum since manufacture: 2 years.

Carta de colores

Wood Products Brochure

Formatos

Containers: 750 ml & 4 L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com