

Ficha Técnica

Glossy Polyurethane Parquet Varnish

Polyurethane Varnish

Versión: 18/08/2023




Descripción

One-component polyurethane varnish for wood subjected to strong abrasion. Glossy and flexible finish. Excellent brushability and good leveling.

Propiedades

- Good Adhesion.
- Good Brushability.
- Fire Resistance test: B-s1, d0.

Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	Colorless
Aspecto	Glossy
Naturaleza	One-Component Polyurethane
Peso específico	1, 02 gr/cm ³

Datos de aplicación del producto

Herramienta	Brush, spray or airless
Rendimiento	12 - 14 m ² /L/Coat
Diluyente	Jafep Polyurethane Solvent
Repintado	24 hours
Secado	1 - 2 hours

Prestaciones finales

Resistencia al frote en húmedo	5
--------------------------------	---

Dónde aplicarlo

Varnishing of interior wood constantly subjected to abrasion, such as parquet, cork floors, stairs, railings, ceiling panels, etc.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current bottle with the next one at 50% to reduce the normal differences between batches.

Modo de empleo



- NEW WOOD:

Sand thoroughly, clean and apply a very diluted first coat. You can reach a dilution of one part of varnish with two of Jafep Polyurethane Solvent. Allow a minimum of 5 hours and a maximum of 24 hours to pass, to apply subsequent layers, after smooth sanding. These topcoats can also be thinned 20-25% with Jafep Polyurethane Thinner.

- VARNISHED WOOD:

Check its compatibility if possible: sand smoothly and varnish. If the varnishes are not compatible or are poorly adhered, they will be completely removed and proceed as on new wood.

Cleaning utensils with polyurethane or xylene solvent.

Almacenamiento

- In its original closed container, at non-extreme temperatures and humidity.
- Keep away from direct sunlight.
- Recommended maximum since manufacture: 2 years.

Formatos

Containers of: 375, 750 ml & 4L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com