

Ficha Técnica

Bathroom Ceiling Paint

Paint with water-repellent effect

Versión: 22/09/2023



Ventajas

- Great Whiteness.
- Good Coverage.
- Water-repellent.
- Breathable.

Descripción

Plastic paint for interiors of great whiteness and good coverage. It has a water-repellent effect and high breathability. It is ideal for use in bathroom ceilings.

Propiedades

Paint for bathroom ceilings is ideal for preventing condensation and the premature appearance of mould, since its formulation incorporates special additives so that, while the surface is water-repellent, it maintains its breathability. It also provides very white finishes with good coverage.

Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Acrylic Copolymers
Peso específico	1,60 ± 0,05 g/cm ³
Viscosidad	7,500 ± 1,000 cp (at Brookfield)

Datos de aplicación del producto

Herramienta	Brush, roller, spray or airless
Rendimiento	7 - 9 m ² /L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	4 – 5 hours
Secado	30 minutes
Curado	28 days

Prestaciones finales

Resistencia al frote en húmedo	Class 5 (Standard UNE-EN 13300); >300 cycles (DIN 53778 standard)
--------------------------------	-------------------------------------------------------------------

Dónde aplicarlo

Matt paint for interiors, with good performance, whiteness and coverage in the painting of all types of interior masonry surfaces: cement and concrete; plaster, brick, etc. It is ideal for painting ceilings and especially bathrooms due to its good breathability and the hydrophobicity or pearl effect it creates.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current can with the next at 50% to reduce the normal differences between batches.



100% Reciclado
Compromiso Medioambiental y Social Jafep



Modo de empleo

ON NEW, CLEAN, DRY SURFACES FREE OF RUST, GREASE OR SALTPETER OF:

Cement and concrete: Once set. Directly, diluting up to 10% for the first coat.

Plaster, plaster or wood: Fixing or sealing previously with products suitable for each case. Diluting up to 10% in the first coat.

ON OLD PAINTED SURFACES:

With paints in good quality condition: Wash and sand lightly, putty if necessary and apply afterwards.

With paintings in poor condition: Remove and proceed as a new surface. If alkalinity is detected on the support, it must be corrected.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep out of direct sunlight.
- Maximum recommended since manufacture: 2 years.

Formatos

Containers: 1 L

Memoria descriptiva

On simple applications

The interior painting and/or decoration of masonry surfaces, mainly bathroom ceilings, will be done with Paint for bathroom ceilings from the company Pinturas Jafep. The yield will be from 7 to 9 m²/L /Coat. The support must be clean, dry and free of rust, dust, grease, salt spray and moisture. The general recommendations of the manufacturer will be respected.



100% Reciclado





Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com