

# ENAMEL RESTORER

## DESCRIPTION

Acrylic enamel high quality water, for restoration of all surfaces.

## PROPERTIES

- White pigmented liquid of high viscosity.
- Unsurpassable hardness and grip.
- Unaffected by cleaning products, resistant to water and vapor.
- Does not turn yellow with time, permanent shine.

## APPLICATIONS

Enamel specially indicated for:

- Restoring chips on porcelain bathtubs and household appliances.

## TECHNICAL CHARACTERISTICS

Viscosity (Brookfield RTV, 20 rpm, Sp.3) at 23°C	Approx. 1.400 mPa s
Superficial Drying Time	20 minutes
Complete drying Time	60 minutes

## INSTRUCTIONS FOR USE

Before using ENAMEL RESTORER make sure that the place where you want to apply the product is clean and dry, rust free and with no remainder of detergent. Shake the product and repair imperfections with the applicator. Do not apply directly to hotplates or any other heat source, even if once dry, this product resists boiling water and vapors.

## STORAGE

Stored in its original container and in a cool, dry place, this product maintains its properties according to the following chart.

Container	PREFERENTIAL PERIOD USE
Plastic bottle	1 Year

## PRESENTATION Visit [www.unecol.com](http://www.unecol.com)

## SAFETY

For further information, see safety data sheets.



Fecha revisión: 2016-07-29

Revisión: 2

The above-mentioned data are based on our current knowledge. They should not be understood as specifications. The user is responsible for checking the suitability of the provided information according to any particular use of the product.

**UNECOLGROUP**

***unecol adhesive ideas s.l.***

Parque Ind. Juan Carlos I. Avenida de la Foia, 44 | 46440 Almussafes | (Valencia) SPAIN | T (+34) 902 99 54 64 F (+34) 902 99 57 20 |



**unecol.com**