

TopSealStone



TopSealStone



Features & Benefits:

- TopSealStone is a colour matched, super strength hybrid adhesive and sealant specially formulated for stone surfaces. It is safe to use on natural and artificial stone including granite, quartz, sandstone, terrazzo, ceramic, marble and porcelain. TopSealStone is plasticiser free so will ensure no edge soiling or staining on natural stone.
- It bonds and seals and so is perfect for installing stone surfaces, upstands and backsplashes. Is suitable for bonding and sealing, for interior and exterior use.
- It cures under the influence of humidity and is flexible once cured forming a durable elastic rubber.
- Fast cure even at low temperatures.
- TopSealStone is an excellent gap

filler and has no shrinkage and is bubble free.

- Bonds even to damp surfaces and is resistant to UV, moisture and mould.
- 10-15 minutes open time.
- TopSealStone contains no isocyanates, solvents and silicones and is environmentally friendly. It is neutral curing and almost odourless.
- TopSealStone has an 18 month shelf life (unopened).

Directions for use:

For Bonding applications:

Apply adhesive in vertical stripes with 10-20cm distance between them. Do not apply adhesive in dots.

For Sealing applications:

Apply an even bead along the area to

be finished and smooth using a tool or soft scraper.

Clean up with soapy solution before skin formation.

Replace cap after use.

Allow to cure for 24 hours before use.

Retailer Opportunity:

TopSealStone can be sold with all kitchen worktop, upstand, backsplash and shower/wall panel installations. No risk of edge soiling or discolouration to all natural stone installations.

As TopSealStone has excellent grab and gap filling properties it is more suitable for fitting backsplashes and upstands then regular silicone. It is easy clean up with soapy solution and so does not leave a surface residue like silicone.



IPS Adhesives Europe Ltd.

New York Way, New York Industrial Park
Newcastle upon Tyne NE27 0QF (UK)
Tel: +44 (0) 191 259 0033
Fax: +44 (0) 191 257 4525
Email: eu.sales@ipsadhesives.com
www.ipsadhesives.com