

Ficha Técnica

Interior-Exterior Alkyd Varnish

Alkyd varnish

Versión: 30/10/2023



Descripción

Alkyd varnish made from alkyd resins, with good adhesion, brushability and penetration, resistant and quick drying. It has a highly decorative transparent finish.

Propiedades

- Good adhesion
- Good brushability
- Good penetration
- High resistance to abrasion, knocks and friction
- Great durability
- Good weather protection
- Fire resistance test: B-s1, d0

Certificados de empresa





Datos técnicos

Datos de identificación del producto

Color	Colorless, rosewood, teak, oak, chestnut, walnut, cherry
Aspecto	Gloss & Satin
Naturaleza	Alkyd Resins

Datos de aplicación del producto

Herramienta	Brush, spray gun or airless
Espesor mínimo	50 - 60 microns dry
Rendimiento	10-14 m ² /L/Coat (Gloss Finish) // 8-12 m ² /L/Coat (Satin Finish)
Diluyente	Jafep White Spirit
Repintado	24 hours
Secado	3-5 hours

Dónde aplicarlo

For varnishing doors, windows, furniture and any wooden surface and obtaining a quality, transparent and silky finish.

Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

Modo de empleo



Shake the container well before using. It is recommended to apply thin layers not exceeding 100 dry microns. The necessary layers can be applied but always respecting the repainting times and the recommended thicknesses of each layer.

- **NEW WOOD:** Clean, sand thoroughly and remove dust. Apply a first coat diluted to 10% and sand again. Apply one or more undiluted coats as a finish.

- **VARNISHED WOOD:** Sand gently and clean. Apply one or two coats without diluting. If it is in very poor condition, the existing varnish will be removed and proceed as new wood.

- Cleaning tools with Jafep White Spirit.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Carta de colores

Varnish Catalogue

Formatos

Containers: 375, 750 ml (Colorless & Colors) & 4 L (Colorless)



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com

