

Ficha Técnica

Nívex

Mat Emulsion Paint

Versión: 30/10/2023



Ventajas

- Resistance and fastness to light.
- Excellent whiteness.
- With anti-mold preservative.

Descripción

High quality emulsion paint. Made with resins and pigments of great resistance and light fastness. It provides particularly white, matte, covering, washable and resistant finishes. Easy application. It is breathable. It contains specific anti-mold preservatives that provide excellent protection to the paint film applied using our anti mould system.

Propiedades

Nívex, thanks to its internal binders that reduce splashing and dripping of the product, results in a paint that is easy to apply and with minimal staining.

Furthermore, the incorporation of specific pigments and additives gives it great resistance and light fastness, allowing it to be used not only indoors but also outdoors. Likewise, they also give it an extraordinary whiteness and very high nuance, classifying it as Deep Matt.

Its formulation includes preservative additives to protect the film.

Certificados de empresa





Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Acrylic copolymers
Peso específico	1,55 ± 0.05 g/cm ³
Viscosidad	12,000 ± 1,500 cp (at Brookfield)

Datos de aplicación del producto

Herramienta	Brush, roller, spray gun or airless
Rendimiento	8-12 m ² /L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	3-4 hours
Secado	30 minutes
Curado	28 days

Prestaciones finales

Resistencia al frote en húmedo	Class 2 (UNE-EN 13300 Standard); >5000 cycles (DIN 53778 Standard)
Aspecto Aplicado	Deep Matt

Dónde aplicarlo

Painting and decoration of masonry surfaces, indoors and outdoors, where a quality, silky, low-odor and easy-to-apply finish is desired.



Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

Modo de empleo

ON NEW CLEAN, DRY AND FREE SURFACES OF RUST, GREASE OR SALITRE OF:

Cement and concrete: Once set. Directly, diluting up to 15% for the first layer.

Plaster, plaster or wood: Fixing or sealing previously with products appropriate to each case. Diluting up to 15% in the first coat.

ON OLD PAINTED SURFACES:

With paints in good quality condition: Wash and sand gently, putty if necessary and then apply.

With paints in poor condition: Remove and proceed as a new surface. If alkalinity is detected in the support, it must be corrected.

** In all cases it is advisable to dilute it to apply it in thin layers, since this will achieve the most optimal results.*

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers: 750 ml, 4 & 15 L

Memoria descriptiva

In simple applications



The painting and/or decoration, especially indoors but also outdoors, of masonry surfaces will be carried out with Nívex Plastic Paint from the Jafep Paints company. The performance will be 8 to 12 m²/L and Coat. The support must be clean, dry and free of rust, dust, grease, salt and moisture. The manufacturer's general recommendations will be respected.



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado

Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com