Ficha Técnica

"Odorless" Anti-stain Finishing Paint

Solvent-based anti-stain paint

Versión: 22/08/2023





Paint made from special alkyd resins, which due to their thixotropic nature, forms a film that isolates moisture stains, oxides, smoke, etc. It is a product to give as a finish and do not use any other product afterwards.

Propiedades

- Odorless.
- Finishing paint.

Certificados de empresa







Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Alkyd Resins
Peso específico	1.45 gr./cm ³

Datos de aplicación del producto

Herramienta	Brush or Roller
Rendimiento	15 - 17 m ² /L/Coat
Diluyente	Jafep Odorless Solvent
Repintado	12 hours
Secado	2 -3 hours

Dónde aplicarlo

Matte paint to apply indoors, both on walls and ceilings with problems of smoke stains, humidity, rust, etc. To use as a finish.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current bottle with the next one at 50% to reduce the normal differences between batches.

Productos relacionados

ODOURLESS SOLVENT

Modo de empleo

ON NEW CLEAN, DRY SURFACES FREE OF RUST, GREASE OR SALTITRE OF:





Cement and concrete: Once set. Directly, diluting up to 10% for the first layer.

Plaster, plaster or wood: Fixing or sealing previously with suitable products for each case. Diluting up to 10% in the first coat.

ON OLD PAINTED SURFACES:

With paints in good quality condition: Wash and sand gently, putty if necessary and apply afterwards.

With paints in poor condition: Eliminate and proceed as a new surface. If alkalinity is detected on the support, it must be corrected.

Almacenamiento

- In its original closed container, at non-extreme temperatures and humidity.
- Keep away from direct sunlight.
- Recommended maximum since manufacture: 2 years.

Formatos

Containers: 750 ml, 4 & 15L







