

# Ficha Técnica

## Protective Wood Undercoat

Protective undercoat for wood

Versión: 21/09/2023



## Ventajas

- Helps preserve wood
- Nourishes the wood
- Improves adhesion
- High resistance to the elements
- Long duration

## Descripción

Colorless water-based preparation for use with both solvent-based and water-based painting systems. It acts deeply on the wood, nourishing it, priming it for subsequent painting and protecting it against insects and parasites, and against destructive fungi and blueing.

## Propiedades

Jafep Protective Undercoat for wood is a water-based product that is ready to use and easy to apply. Protects wood against wood-destroying fungi and blue-blue fungi, and also against insects (termites).

## Certificados de empresa



## Datos técnicos

### Datos de identificación del producto

Color	Colorless
Aspecto	Liquid
Naturaleza	Biocide
Peso específico	0.95-1.05g/cm <sup>3</sup>

### Datos de aplicación del producto

Herramienta	Brush, Roller
Repintado	24 hours
Secado	1-2 hours

### Prestaciones finales

Aspecto Aplicado	Colorless, leaves no film
------------------	---------------------------

## Dónde aplicarlo

Jafep Protective undercoat for wood is intended for the treatment of exterior wood such as windows, exterior doors, siding, fences, etc. Direct contact with the soil and aquatic environment should be avoided.

## Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply if the relative humidity is greater than 80%.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Use only in doses of 200 ml/m<sup>2</sup> with application by brush and/or roller.
- Do not use on wooden pieces in direct contact with food or feed.
- Do not use indoors, treated wood should only be used indoors for exterior window and door frames.
- Do not use near aquatic environments such as streams, lakes, etc.

## Modo de empleo

The application must always be for exterior, both Jafep Protective wood undercoat and its subsequent finishing layer



(Only for Class 2 and 3 uses according to DS/EN335:2013).

Clean, sand and remove dust. In the case of painted wood, strip it completely. Apply with a brush or roller. Apply without diluting and after 24 hours of application, always finish with a finishing product (varnish, lasur, etc.).

A dosage of 200 ml product/m<sup>2</sup> is recommended, without exceeding it.

To clean the tools, use mild soap and water.

## Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

## Formatos

Containers: 750 ml & 2,5 L



*Atención al Cliente*

**967 44 05 96**

atencionalcliente@jafep.com



*Servicio Técnico*

dpto\_tecnico@jafep.com



100% Reciclado  
Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com  
jafep@jafep.com