Ficha Técnica

Quick Drying Industrial Alkyd Enamel





Ventajas

- Fast dry
- High brightness
- Good coverage
- Allows handling of painted parts

Descripción

Industrial finishing enamel for metal structures, pipes, machinery, etc. Made with special modified alkyd resins and highly resistant pigments that provide high gloss, good coverage and quick drying, which allows the workability of the painted pieces.

Propiedades

- High brightness
- Good coverage
- Easy application, good leveling and low sag
- Allows quick handling of painted parts
- Good resistance to friction

Certificados de empresa



ARGENTINA





Datos técnicos

Datos de identificación del producto

Color	White, Black and all the colors of our Industrial Tintometric System
Aspecto	Gloss
Naturaleza	Modified alkyd resins
Peso específico	1,00-1,20 gr/cm³ depending on colors

Datos de aplicación del producto

Rendimiento	8-10 m ² /Kg (10-12 m ² /L.)
Diluyente	Jafep White Spirit
Repintado	24 hours
Secado	15 - 20 minutes

Dónde aplicarlo

Industrial finishing paint for metal structures, pipes, machinery, etc. Its quick drying allows the painted pieces to be handled.

Practical (actual) performance will depend on film thickness, nature of substrate and application method.

Modo de empleo

It is mainly applied to spray guns, airless, etc.

Stir the contents of the container, dilute appropriately and apply preferably with a spray gun.

The surfaces must be clean, dry, degreased and free of rust; adequately protected with a synthetic alkyd primer if they are ferrous or with an adequate preparation if they are galvanized or alloys.

If it is a repaint in good condition, clean properly and then apply.

If it is in poor condition, remove it and proceed as a new surface.

DUBAI





Formatos

Containers: 750ml, 4 & 15 L







