

# Ficha Técnica

## 2000 Satin

Satin Emulsion Paint

Versión: 31/10/2023



## Descripción

Emulsion paint for interior and exterior of high quality, stability and resistance, which provides a waterproof and durable finish with excellent whiteness and good covering power. Satin and silky final appearance. Very washable.

## Propiedades

- Waterproof and durable finish.
- Excellent whiteness.
- Good covering power.

## Certificados de empresa



## Datos técnicos

### Datos de identificación del producto

Color	White
Aspecto	Satin
Naturaleza	Vinyl copolymers
Peso específico	1.25 gr./cm <sup>3</sup>

### Datos de aplicación del producto

Herramienta	Brush, roller, spray gun or airless
Rendimiento	10-15 m <sup>2</sup> /L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	7 hours
Secado	30 - 45 minutes

## Dónde aplicarlo

Quality paint, with excellent results in terms of whiteness, coverage and washability on all types of surfaces, walls and ceilings, leaving a pleasant satin and silky appearance, on smooth or rough surfaces (gotelé, pitted, scratched, etc.) and a effective outdoor protection.

## Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

## Productos relacionados

THIXOTROPIC SYNTHETIC SEALER  
Sellacryl Penetrating Acrylic Varnish and Fixer



# Modo de empleo

## NEW UNPAINTED SURFACES

On new clean and dry surfaces, free of rust and grease from:

Cement and concrete: We check that the concrete is completely set. If it is new, wait approximately 30 days. It will be applied directly, diluting up to 25% for the first layer (as a primer).

Mortars: Eliminate possible efflorescence and possible alkalinity through appropriate treatment. It is always advisable to apply a Sellacryl type fixative.

Plaster and plaster: Fixing previously with Sellacryl JAFEP. If, in addition to being very porous, a very fragile plaster is observed, it may be advisable to apply Solvent-Fixing Primer.

Wood: Fix previously with Synthetic Sealer or Water Sealer.

## PAINTED SURFACES

With quality paints in good condition: Wash and sand gently, in order to tone down those that have a satin or shiny appearance and to facilitate pore opening and adhesion. Apply below.

With paints in poor condition: Remove, apply a Sellacryl-type fixative and proceed as if it were a new surface. If they have defects such as chalking, chipping, cracking, etc., eliminate them. If they present mold or even algae, they must be removed and completely disinfected. You can use diluted bleach (domestic) or JAFEP Mold Cleaner.

On tempera, glue or lime paints: They must be completely removed. Repair irregularities, chips and other damage with JAFEP powder or ready-to-use fillers and proceed as a new surface.

# Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

# Formatos

Containers: 750 ml; 4, 8 & 15 L





*Atención al Cliente*

**967 44 05 96**

atencionalcliente@jafep.com



*Servicio Técnico*

**dpto\_tecnico@jafep.com**



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



[www.jafep.com](http://www.jafep.com)  
[jafep@jafep.com](mailto:jafep@jafep.com)