

Ficha Técnica

Sellacryl Penetrating Acrylic Varnish and Fixer



Acrylic Sealant

Versión: 18/08/2023




Ventajas

- Great Holding Power
- Prevents Moisture Penetration

Descripción

Petrifying varnish based on acrylic resins, very appropriate for the preparation of porous surfaces. Prevents moisture penetration into the interior and eliminates moisture. It serves as a sealer for walls, bricks, paints, etc. 100% acrylic product that, when applied on concrete, prevents the entry of CO₂ and therefore the carbonation process. With the appropriate dilution in each case, it is especially indicated for the preparation of all types of construction materials.

Certificados de empresa



Datos técnicos

Datos de identificación del producto



Color	Colorless
Aspecto	Matt
Naturaleza	Acrylic emulsion
Peso específico	1.30 gr./cm ³

Datos de aplicación del producto

Herramienta	Brush or Roller
Rendimiento	10 - 12 m ² /L/Coat
Diluyente	Thinner for water-based paints and enamels
Repintado	8 hours
Secado	2-4 hours

Dónde aplicarlo

Ideal for sealing all types of concrete, brick, plaster, plaster surfaces, etc.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current bottle with the next one at 50% to reduce the normal differences between batches.

Modo de empleo

It can be applied by brush or roller. If it is applied as a primer or fixative, it must be lowered in a ratio of 1:3 with Diluent for water-based paints and enamels, as a minimum, and it can even go up to 1:7. If it is used as an effective anti-carbonation finish, we must leave a real dry film of between 80 and 100 microns. It can be given directly or discounted up to 50%. To clean brushes or rollers, use only water.

Almacenamiento

- In its original closed container, at non-extreme temperatures and humidity.
- Keep away from direct sunlight.
- Recommended maximum since manufacture: 2 years.



Formatos

Plastic containers of: 750 mL; 4L; 8L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado

Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com