

Ficha Técnica

Wood Effect Enamel

Synthetic lacquer enamel

Versión: 31/10/2023



Ventajas

- Easy application
- Ready to use
- All kinds of surfaces

Descripción

Alkyd lacquer enamel that imitates wood grain with a single coat. Easy to apply regardless of whether the surface is poreless or lacquered (doors, frames, cabinets, windows, appliances, etc.)

Propiedades

It has good brushability, which makes its application very comfortable. It also has high covering power, good washability and antioxidant properties, making it suitable for both indoor and outdoor applications. Its excellent adhesion and hardness give it great resistance to friction and atmospheric agents.

Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	Light Walnut, Ash Oak, Wenge and Walnut
Naturaleza	Alkyd resins
Peso específico	1.00 ± 0.05 g/cm ³

Datos de aplicación del producto

Herramienta	Brush
Rendimiento	8-10 m ² /L/Coat
Diluyente	Not required, product ready to use.
Repintado	24 hours
Secado	6-8 hours

Prestaciones finales

Aspecto Aplicado	Satin
------------------	-------

Precauciones

- Do not apply at temperatures below 5 °C or above 30 °C.
- Do not apply at risk of frost or rain.
- Do not apply in strong wind conditions or under direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current jar with the next one 50% to reduce the normal differences between batches.

Modo de empleo

The surface must be completely clean, dry and free of grease. In non-porous materials, it will be sanded with the necessary tool. Depending on the type of support, we will use the appropriate primer, ensuring that it is well adhered and dry.

Mix the product well before using it, and without diluting it. Using a 7 to 8 cm simple brush with natural bristles, apply an abundant and uniform layer that will be finished with long brush strokes in the desired direction to mark the grain, gently passing the tip of the brush in continuous, parallel or slightly wavy in the same direction.

If we want to mark the grain more, we can make some irregular cuts on the shoulder and proceed in the same way.



Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers: 750 ml



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado

Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com